

S32 UVD

Specification Sheet

The ErosionControlBlanket S32 UVD is an ultra short-term double net straw fiber erosion control blanket designed for use on moderate slope and channel applications requiring erosion control for up to 3 months depending on moisture, light, and environmental conditions. The blanket is sewn together on 1.5 inch (38.1 mm) centers. The S32 UVD meets all requirements established in the FHWA FP-03 as a Type 1D erosion control blanket for use on slopes with gradients not exceeding 2:1 (h:v) and has been tested by the National Transportation Product Evaluation Program (NTPEP). The S32 UVD comes packaged in clear shrink-wrap with a blue band and includes installation instructions.

Product Nomenclature & Properties

- **S** = 100% agricultural straw fiber matrix
- **3** = straw fiber matrix applied at a rate of 0.5 lbs/yd^2 (270 g/m²)
- 2 = top and bottom rapid photodegradable nets with a mesh size of 0.588 x 0.5 in (1.49 x 1.3 cm)
- **UVD** = rapid photodegradable nets and thread to ensure consistent functional longevity

Index & Bench Scale Testing

Test Description	Test Method	Test Results	
Mass per Unit Area	ASTM D6475	8.74 oz/yd ²	
Tensile Strength	ASTM D6818	11.3 lbs/in @ 21.9% MD 5.6 lbs/in @ 14.6% TD	
Thickness	ASTM D6525	0.372 in	
Light Penetration / Ground Cover	ASTM D6567	5.4% / 94.6%	
Water Absorption	ASTM D 1117 & ECTCTASC 00197	496%	
Unvegetated Bench-Scale Rain Splash and Runoff (not to be used as a design value)	ASTM D7101	Soil Loss Ratio* = 11.27 Soil Loss Ratio* = 12.56 Soil Loss Ratio* = 14.00	
Unvegetated Bench-Scale Shear Stress (not to be used as design value)	ASTM D7207	1.49 lbs/ft ² @ 1/2 in. soil loss	
Seed Germination and Plant Growth Under Bench-Scale Conditions	ASTM D7322	527% Improvement (increased biomass)	
*Soil Loss Ratio = Soil Loss Bare Soil / Soil Loss with RECP = 1 / C-Factor (Note: Soil loss is based on regression analysis)			

Design Values

- "C" factor = 0.005
- Maximum Permissible Shear Stress = 84 Pa (1.75 lbs/ft²)
- Maximum Permissible Velocity = 6 ft./sec. (1.83 m/s)
- Manning's "n" = 0.03

Standard Roll Details

Width	2.44m (8 ft)	4.88m (16 ft)
Standard Length	34.3m (112.5 ft) 83.61m ² (100 yd ²)	34.3m (112.5 ft)
Area	83.61m ² (100 yd ²)	167.23m ² (200 yd ²)
Weight ±10%	25kg (54 lb)	50kg (108 lb)

"Big Daddy" Roll Details

Width	2.44m (8 ft)	4.88m (16 ft)
Standard Length	171.49m (562.5 ft)	171.49m (562.5 ft)
Area	418m ² (500 yd ²)	836m ² (1000 yd ²)
Weight ±10%	122.5kg (270 lb)	244.94kg (540 lb)